

FIX 51

HOT MELT GLUE GUN

Hot melt glue gun with 6 glue sticks of 11 mm diameter for gluing, decorating, modelling and household repairs. For gluing of wood, paper, cardboard, fabrics, metal, plastics and other materials.

PROPERTIES

- For glue sticks of 11 mm diameter.
- Heat insulated nozzle.
- Built-in valve which prevents uncontrolled dripping of alue.
- Built-in stand.
- Ergonomic handling.
- Fast curing of FIX glue sticks.
- Transparent, elastic and strong joint.

TESTS AND CERTIFICATES

- EMC Certificate of Conformity: Electromagnetic Compatibility Directive
- LVD Certificate of Conformity: Low Voltage Directive

AREA OF USE

- For gluing of wood, paper, cardboard, fabrics, metal, plastics and other materials.
- Not suitable for PP, PE, soft PVC and styrofoam.

TECHNICAL DATA

Hot melt glue gun:

Mains voltage220-240 VWorking power12 WHeating power70 WOperating temperaturemax. 190 °CHeating time8-10 minutesWeight202 q

Glue sticks:

Chemical basis Adhesive/adhesive film colour Charge diameter

Length

Viscosity at 180 °C, ASTM D-3236 Softening point, R&B: ASTM E-28

Operating temperature

Density

copolymer of ethylene – vinyl acetate white-transparent/transparent

- ≈ 11.5 mm
- ≈ 200 mm

7000-7000 mPa s

87 ± 5 °C

180 - 200 °C

 $\approx 0.98 \text{ g/cm}^3$













INSTRUCTIONS FOR USE

- Surfaces must be clean and free of dust and grease. Grinding smooth surfaces increases the strength of
 joints. It is recommended to heat the metal surfaces slightly before gluing. Before gluing, we recommend
 testing on the material to be glued.
- Check that the gun is undamaged or whether the cord is damaged.
- Check that the gun nozzle is clean and remove any adhesive residue before use.
- Put the gun on a stand and then on a wooden ground.
- Insert FIX glue stick and warm up the gun for 8-10 minutes.
- Squeeze the trigger, apply the glue on one side only and join the surfaces immediately.
- The open time of the adhesive depends on the type of material, the temperature and quantity of the adhesive, the temperature of the material and the working environment. It ranges from 20 120 s, so the adhesive is hardened in less than 2 minutes.
- Warning: Liquid adhesive can reach up to 200 °C. Danger of burns.

PACKAGING

Hot melt glue gun and 6 glue sticks in a box.

STORAGE

Glue sticks: 36 months in a dry place at temperatures up to 25 °C, away from heat sources.

HEALTH, SAFETY, HANDLING AND DISPOSAL INFORMATION

Additional safety information, safe handling instructions, information on personal protective equipment, and disposal information can be found in the safety data sheet. Safety data sheet available on request. You can also obtain a copy from your TKK sales representative.

WARNING

The information given is based on our tests and practical experience. However, due to specific conditions and working methods we recommend preliminary tests for each case of use.



